



ADB-5810WX

HD IPTV recorder with home-networking capabilities



HIGHLIGHTS

Intuitive User Interface via browser

Interactivity through leading IPTV middleware

Ethernet, USB 2.0 and HDMI™ interfaces

ADB. INSPIRING HYBRID PAY-TV

ADB-5810WX

HD IPTV recorder with home-networking capabilities

The ADB-5810WX is a high definition and standard definition recorder optimized for IP networks. The unit works with the industry's leading conditional access, digital rights management and middleware technologies.

The on-screen navigation of the ADB-5810WX provides a simple and intuitive user interface for managing recordings and favorite channels.

The ADB-5810WX is the heart of your multi-room, home networking system, connecting to other devices to share the content stored on its hard disk, and letting other set-top boxes schedule recordings.

For HCNA networking capabilities, see ADB's 5721WXX.

TECHNICAL SPECIFICATIONS

TV Reception

- IPTV

System Resources

- FLASH memory: Up to 64MB
- RAM memory: Up to 256MB (DDR)
- Up to 320GB built-in Hard Disk Drive (HDD)

Software

- Linux , Mozilla Browser
- ADB JavaScript API for IPTV and DVB
- Selection of IPTV middleware
- Compatible with MS Windows CE 5.0 BSP
- Advanced Graphical User Interface
- UPnP Media Player & Server
- Video Telephony
- HDD MP3 Player & Photo Album
- Electronic Program Guide
- Picture in Picture functionality

Security

- CGMS-A on analog outputs
- Selection of embedded DRM & Conditional Access
- Macrovision on SD output
- HDCP on HDMI output
- Pairing of the HDD with the STB
- Secure Video Processor (SVP)

IP Protocols & Standards

- IGMP2 [RFC 2236], IGMP3 [RFC 3376]
- RTSP [RFC 2326]
- RTP [RFC 3550]
- PPPoE [RFC 2516]
- SIP [RFC2543]
- NTP [RFC 1305]
- SSL 3.0
- TLS 1.0 [RFC 2246]
- HTTP 1.1, HTTPS, HTTP Authentication [RFC 2617]

- DHCP [RFC 2131]
- HTML 4.01, Dynamic HTML
- XHTML 1.0
- JavaScript 1.5
- DOM level 2
- CSS level 2
- TR-069/TR-111

Video

- MPEG-1 (SD)
- MPEG-2 MP@ML (SD) and MP@HL (HD)
- MPEG-4 p.10 (H.264) MP@L3 (SD) and MP@L4.1 (HD)
- H.263 decoding and encoding for video telephony
- SMPTE VC-1 SP@LL, MP@LL, MP@ML, MP@HL,
- AP@L1-3
- Video format: 4:3, 16:9 with Pan Scan, Letterbox
- Up-scaling of SD video on HD output
- Downscaling HD video on SD output
- Resolution: up to 1920x1080
- 32-bit color for OSD graphics and external applications

Audio

- MPEG-1 Layers I, II, III (MP3)
- MPEG-2 Layer 2
- MPEG-2 AAC LC and AAC+
- MPEG-4 AAC LC 2-channel/5.1 channel, MPEG-4
- AAC+SBR 2-channel/5.1 channel
- WMA-9, WMA-9 Pro
- G.7xx for VoIP
- Echo cancellation for VoIP
- Mono, Dual Mono, Stereo, Joint Stereo
- Dolby Digital pass-through to external decoder
- Dolby Digital Down-mix

Return Channel

- IEEE 802.3 10/100 Ethernet interface

Front Panel

- 9 navigation keys
- 4 segment display
- STB status LED indicators
- Optional USB 2.0

Back Panel Connectors

- RF Modulator & Loop-thru output
- TV & VCR 3 x RCA output
- S-Video output
- YPrPb high definition output
- HDMI high definition output
- Digital S/PDIF optical audio output
- USB 2.0
- RJ-45 Ethernet port
- DC power input

Accessories

- Remote Control
- Batteries
- Power Cord with PSU
- Quick Install Manual
- Audio/Video cables (opt.)
- Ethernet cable (opt.)
- User Manual (opt.)

General Data

- Operating temperature range +5 to +40(°C)
- AC input voltage: 90 - 264 V, 50/60 Hz
- Dimensions: 12.8" x 2.4" x 10"
- FCC, UL & CUL compliance

Advanced Digital Broadcast

10901 W. 120th Avenue, Suite 230,
Broomfield, CO 80021
USA

Tel: +1 303 474 8600

Fax: +1 303 474 8687

HDMI™, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.
Dolby and the double-D symbol are trademarks of Dolby Laboratories.
UPnP is a trademark of the UPnP Forum.
DLNA is a trademark of the DLNA Organization.
Carbo™ and Smooth-View™ are trademarks of ADB S.A.
ADB S.A. reserves the right to change, modify or enhance this specification at any time without prior written notice.
ADB S.A. is a member of ADB Group (www.adbholdings.com).
© 2010 Advanced Digital Broadcast